

# IndeeLift®

*The People Picker Upper!*

## FTS-600 Floor-to-Stand For Professional Healthcare



**The FTS-600 is a fall recovery and transfer appliance designed to eliminate manual patient lifting.**

- For fall recovery, the FTS-600 can raise individuals weighing up to 600 lbs. (272 kg) from the floor to a seated or standing position, and allows for safe seated transfers to and from a wheelchair, bed commode or other surfaces such as an exercise mat.
- Engineered to lift a patient standing on its platform from the floor to a height that will allow access to a radiology or exam table.
- Supports Safe Patient Handling and Mobility Standards to keep staff safe from lift injuries.



### Maintains Patient Dignity and Safety



# Summary of Features

- Lifts up to 600 pounds from floor to standing in about 90 seconds
- Beveled seat-front for easy slide on transfer surface
- Wired remote for convenient operation
- Swinging/Removable Rise Assist Handles for secure transfers
- Powder coated for easy cleaning
- Tight turning radius to get into small spaces
- Small footprint for easy storage
- Safety belts provided for added safety during lifts
- Dual lithium batteries for uninterrupted operations
- Status check in each battery that shows its current charge level
- Automatic charger to leave the second battery on until time to swap



**Lithium-Ion Battery Pack**

## Physical Specifications

Safe Working Load.....	600 lbs. (272 kg)
Overall Depth.....	26.5" (67 cm)
Maximum Overall Height (raised).....	84.75" (183 cm)
Minimum Overall Height (lowered).....	43.75" (107 cm)
External Width incl Rise-Assist Handles..	23" (58 cm)
Maximum Seat Height.....	30" (76 cm)
Seat Width.....	22" (56 cm)
Wheel Diameter.....	6" (15 cm)
Unit Weight.....	82 lbs. (37 kg)

## Electrical Specifications

Standard 2-prong 110 VAC Power Cord (USA)  
 Standard 2-prong 220 VAC Power Cord (International)  
 Operating Environment: >+5 °C <+40 °C (41° to 104°F)  
 Lithium-Ion Battery: 24 VDC

